

10-6A Nylon Flock

Description:

Employed as a sound deadening material, but can also provide a velvet-like finish that adds a luxurious touch to different substrates. Flock can be requested in a variety of colors.

Product Construction:

Strong abrasion resistant poly-cotton flock offers exceptional anti-squeak to many applications. A very aggressive adhesive to low surface energies offers high initial tack. Low fogging qualities and moisture stable.

Typical Properties:

Liner:	Polyester
Liner Thickness:	2.0 mil
Adhesive:	Acrylic
Carrier:	Black Flock
Adhesive & Carrier Thickness:	35.5 mil
Total Thickness:	37.5 mil
Min Application Temp:	50°F / 10°C
Max Continuous Operating Temp:	200°F / 93°C
Max Intermittent Operating Temp:	250°F / 121°C

OEM Standards:

Testing may be required

Chrysler: MS JZ8 22 & PF 10770

Ford: ESB M6G17 & WSS M15P4 F

GM: 9985281

GMW: 16443 Type 1 & 2, 16875 Type 1A

Rev. 1

WALCO MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The Typical Properties listed above are not to be construed as specification. User is responsible for determining whether the Walco product is fit for a particular purpose and is suitable for a user's method of application. Walco assumes no obligations or liability for any advice furnished by it, or for results obtained with respect to any product(s). All such advice is given at the buyer's risk, regardless of the legal theory asserted.

Limitation of Remedies and Liability: If the Walco product is proved to be defective, THE EXCLUSIVE REMEDY, AT WALCO'S OPTION, SHALL BE TO REFUND NO MORE THAN THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE WALCO PRODUCT PROVEN TO BE DEFECTIVE. In no event shall Walco be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability. No waiver, alteration, additions or modifications of the foregoing conditions shall be valid unless made in writing and manually signed by an officer of Walco Corporation.