

10-7

Ultra-High Molecular Weight Polyethylene Film

Description:

Virtually indestructable abrasion resistant film tape. Best choice for resolving issues concerning metal to metal squeaks and abrasion. Low friction surface enhances noise suppression. Available in roll form (no liner) and perforated. User friendly die cuts with and without adhesive. Furnished in natural or black.

Product Construction:	3 Mil	5 Mil	10 Mil
Duty:	Light Duty	Medium Duty	Heavy Duty
Adhesive:	Acrylic	Acrylic	Acrylic
Elongation:	300%	300%	300%
Tensile Strength:	20 lb./in.	33 lb./in.	65 lb./in.
Co-Efficient Friction:	<.1	<.1	<.1
Continuous Temp. Range:	-40°F to 200°F	-40°F to 200°F	-40°F to 200°F

OEM Standards:

Testing may be required

Chrysler: MS CH612

Ford: ESB M3G123 B

GM: 6419 Type 2 Cycle D

GMW: 16879

Rev. 1

WALCO MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The Typical Properties listed above are not to be construed as specification. User is responsible for determining whether the Walco product is fit for a particular purpose and is suitable for a user's method of application. Walco assumes no obligations or liability for any advice furnished by it, or for results obtained with respect to any product(s). All such advice is given at the buyer's risk, regardless of the legal theory asserted.

Limitation of Remedies and Liability: If the Walco product is proved to be defective, THE EXCLUSIVE REMEDY, AT WALCO'S OPTION, SHALL BE TO REFUND NO MORE THAN THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE WALCO PRODUCT PROVEN TO BE DEFECTIVE. In no event shall Walco be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability. No waiver, alteration, additions or modifications of the foregoing conditions shall be valid unless made in writing and manually signed by an officer of Walco Corporation.